

SAFETY DATA SHEET

Revision Date 26-Mar-2020 Version 1

1. IDENTIFICATION

Product identifier

Product Name AUTO MAGIC PC-1 EXTRA CUT RUBBING COMPOUND

Other means of identification

Product Code 501201

Recommended use of the chemical and restrictions on use

Recommended Use Automotive Rubbing Compound. For professional use only.

Uses advised againstUses other than recommended use.

Details of the supplier of the safety data sheet

Manufacturer Address

ITW Evercoat 6600 Cornell Road Cincinnati, Ohio 45242 Telephone: 513-489-7600

24-hour emergency phone number CHEMTREC: 1-800-424-9300 INTERNATIONAL: 1-703-527-3887

E-mail address: Info@automagic.com

May Also Be Distributed by:

ITW Permatex Canada 101-2360 Bristol Circle

Oakville, ON Canada L6H 6M5 Telephone: (800) 924-6994

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids Category 4

Label elements

Emergency Overview

Signal word Warning

Combustible liquid

Appearance Grey paste Physical state Liquid Odor Fruity

Precautionary Statements - Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking Wear protective gloves/protective clothing/eye protection/face protection

In case of fire: Use CO2, dry chemical, or foam to extinguish.

Precautionary Statements - Storage

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Harmful to aquatic life with long lasting effects. Harmful to aquatic life.

Unknown acute toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Aluminum Oxide	1344-28-1	15 - 40
Glycerine	56-81-5	1 - 5

4. FIRST AID MEASURES

Description of first aid measures

General advice Call 911 or emergency medical service. Remove and isolate contaminated clothing and

shoes.

Eye contact In case of contact with substance, immediately flush skin or eyes with running water for at

least 20 minutes.

Skin contact Wash skin with soap and water.

Inhalation Move victim to fresh air. If breathing is irregular or stopped, administer artificial respiration.

Administer oxygen if breathing is difficult.

Ingestion Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth

to an unconscious person. Call a physician. Do NOT induce vomiting.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved and take precautions to

protect themselves.

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physicians Keep victim warm and quiet.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Dry chemical, CO2, water spray or regular foam, Water spray, fog or regular foam, Use water spray or fog; do not use straight streams, Move containers from fire area if you can do it without risk

Unsuitable extinguishing media

CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than

COMPOUND

air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Those substances designated with a "P" may polymerize explosively when heated or involved in a fire. Runoff to sewer may create fire or explosion hazard. Substance may be transported hot.

Explosion data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

All equipment used when handling the product must be grounded. Do not touch or walk

Revision Date 26-Mar-2020

through spilled material. Stop leak if you can do it without risk.

Other Information Water spray may reduce vapor; but may not prevent ignition in closed spaces.

Environmental precautions

Environmental precautions Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up

Methods for containment A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth,

sand or other non-combustible material and transfer to containers. Dike far ahead of liquid

spill for later disposal.

Methods for cleaning up

Use clean non-sparking tools to collect absorbed material.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

grounded. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use

personal protective equipment as required. Do not breathe

dust/fume/gas/mist/vapors/spray. Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapors).

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity). Keep containers tightly closed in a cool, well-ventilated place.

Keep away from heat. Keep in properly labeled containers.

Incompatible materials Strong oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines .

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH

Aluminum Oxide 1344-28-1	TWA: 1 mg/m³ respirable particulate matter	TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable fraction	-
		(vacated) TWA: 10 mg/m³ total dust	
		(vacated) TWA: 5 mg/m³ respirable	
		fraction	
Glycerine	-	TWA: 15 mg/m ³ mist, total	-
56-81-5		particulate	
		TWA: 5 mg/m³ mist, respirable	
		fraction	
		(vacated) TWA: 10 mg/m ³ mist,	
		total particulate	
		(vacated) TWA: 5 mg/m ³ mist,	
		respirable fraction	

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Skin and body protection Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

Respiratory protectionUse NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

General Hygiene Considerations When using do not eat, drink or smoke. Regular cleaning of equipment, work area and

clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state Liquid
Appearance Grey paste
Odor Fruity

Odor threshold No information available

Property Values Remarks • Method

pH

Melting point / freezing pointNo information availableBoiling point / boiling range100 °C / 212 °FFlash point73 °C / 163 °FEvaporation rateNo information availableFlammability (solid, gas)No information available

Flammability Limit in Air

Upper flammability limit: 0.5% Lower flammability limit: 7%

Vapor pressureNo information availableVapor densityNo information availableRelative densityNo information available

Water solubility Miscible in water

Solubility(ies) No information available
Partition coefficient No information available
Autoignition temperature No information available

501201 - AUTO MAGIC PC-1 EXTRA CUT RUBBING COMPOUND

Revision Date 26-Mar-2020

Decomposition temperatureNo information availableKinematic viscosityNo information availableDynamic viscosityNo information availableExplosive propertiesNo information availableOxidizing propertiesNo information available

Other Information

Softening point
Molecular weight
No information available
SADT (self-accelerating
No information available

decomposition temperature)

10. STABILITY AND REACTIVITY

Reactivity

No information available

Chemical stability

Stable under normal conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents

Hazardous Decomposition Products

Carbon oxides

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation May cause irritation of respiratory tract.

Eye contact Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact May cause skin irritation and/or dermatitis.

Ingestion Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Aluminum Oxide	> 5000 mg/kg (Rat)	-	-
1344-28-1			
Glycerine	= 12600 mg/kg (Rat)	> 10 g/kg (Rabbit)	> 570 mg/m³ (Rat) 1 h
56-81-5			

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Germ cell mutagenicity No information available.

CarcinogenicityThe table below indicates whether each agency has listed any ingredient as a carcinogen.

CONFOUND

Revision Date 26-Mar-2020

Target Organ Effects Eyes, kidney, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 10201 mg/kg ATEmix (dermal) 36919 mg/kg ATEmix (inhalation-dust/mist) 40.7 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

3.89 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical Name	Partition coefficient
Glycerine	-1.76
56-81-5	

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number U122

14. TRANSPORT INFORMATION

Note: This information is not intended to convey all specific regulatory information relating to this product.

Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. It is the responsibility of the transporting organization to follow all

applicable laws, regulations and rules relating to the transportation of the material.

<u>DOT</u>

UN/ID No NA1993

Proper shipping name Combustible Liquids, n.o.s, (Hydrocarbons)

Packing Group

IATA

Proper shipping name Not regulated

IMDG

Proper shipping name Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies **DSL/NDSL** Complies **EINECS/ELINCS** Complies Complies **ENCS** Complies **IECSC** Complies **KECL PICCS** Complies **AICS** Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %	
Aluminum Oxide - 1344-28-1	1.0	
Formaldehyde - 50-00-0	0.1	

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
	Carcinogen
50-00-0	

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Aluminum Oxide 1344-28-1	X	X	X
Glycerine 56-81-5	Х	X	X
Formaldehyde 50-00-0	Х	Х	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 1 Flammability 2 Instability 0 -

HMIS Health hazards 1 Flammability 2 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date 26-Mar-2020

Disclaimer

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

End of Safety Data Sheet