



PROFESSIONAL

Pro Speed Compound

- Fast cutting compound with advanced technology
- Quick removal of 1200 grit and finer sanding marks for easier polishing
- · Removes deep scratches, acid rain or severe swirls/holograms
- Works great on fresh & cured paints

FOR PROFESSIONAL USE ONLY NOT INTENDED FOR RETAIL SALE

Fast cutting body shop safe compound with advanced technology designed for Professionals. DIRECTIONS: SHAKE WELL. For best results, PRECAUTIONS:

apply to a clean, cool properly cured paint surface.

- 1. Set rotary buffer to approximately 1200 - 1800 RPM's and work one section at a time using your favorite Meguiar's Wool Cutting Pad.
- 2. Apply Pro Speed Compound (M100) directly to the paint surface and begin working in a 2' x 2' area with overlapping passes. Buff area using light to medium pressure. Reduce pressure when compound begins to dry. Continue working until defects or sanding marks are removed.
- 3. Wipe off remaining residue with a Meguiar's Ultimate Wipe (M9910) prior to polishing.
- 4. For final polishing, please choose the appropriate Meguiar's Foam Pad and your favorite Meguiar's polish.

PROFESSIONAL TIP: For best results be sure to remove any compound residue off all door jamb areas before moving on to polishing the surface. Additionally, for optimal results, clean pads frequently using a soft nylon bristle brush.



WARNING. Causes skin irritation. May cause drowsiness or dizziness.

PRECAUTIONS: Avoid breathing dust or vapors. Use only outdoors or in a well-ventilated area. Wear protective gloves. Wash thoroughly after handling. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents and container in accordance with applicable local regulations. KEEP OUT OF REACH OF CHILDREN.

FIRST AID: If inhaled: Remove person to fresh air and keep comfortable for breathing. If on skin: Wash with plenty of soap and water. If skin irritation occurs: Get medical attention. Take off irritation occurs: Get medical attention. Take off contaminated clothing and wash it before reuse. Call a poison center or physician if you feel unwell. CONTAINS: WATER (7732-18-5); PETROLEUM DISTILLATES (64742-48-9); ALUMINUM OXIDE (1344-28-1); PETROLEUM DISTILLATES (64742-47-8); CONDITIONERS (TRADE SECRET); WHITE MINERAL CONDITIONERS (TRADE SECRET); WHITE MINERAL CONDITIONERS (TRADE SECRET); GLYCERIN (56-81-5); TRIETHANOLAMINE (102-71-6). SUPPLEMENTAL INFORMATION: 1% of the mixture consists of ingredients of unknown acute oral toxicity, 3% of the mixture consists of ingredients of unknown acute dermal toxicity.

of unknown acute dermal toxicity.



VSLM100 © Meguiar's Inc. Irvine, CA 92614 meguiars.com CarCrazyCentral.com

Meguiar's UK 3 Lamport Court, Heartlands Daventry, Northants, NNII 8UF meguiars.com/international