



MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number 676-003
Product name **Carpet Spot Plus**
Effective date 11-Feb-2011
Company information Sprayway, Inc.
1005 Westgate
Addison, IL 60101 United States
Company phone General Assistance 630-543-7600
Emergency telephone US 800-424-9300
Emergency telephone outside US 703-527-3887
Version # 07
Supersedes date 11-Feb-2011

2. Hazards Identification

Emergency overview Aerosol. CONTENTS UNDER PRESSURE.
Harmful in contact with eyes. May be harmful if absorbed through skin.

Potential health effects

Routes of exposure Eye contact. Inhalation. Skin contact. Ingestion.

Eyes Contact may irritate or burn eyes. Eye contact may result in corneal injury.

Skin May be harmful if absorbed through skin. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

Ingestion Exposure by ingestion of an aerosol is unlikely. May cause delayed lung damage. Components of the product may be absorbed into the body by ingestion.

Target organs 2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged and may cause blood damage. These effects have not been observed in humans.

Chronic effects Central nervous system. Lungs.
Unconsciousness. Conjunctiva. Cyanosis (blue tissue condition, nails, lips, and/or skin). May be harmful if absorbed through skin. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. May cause delayed lung injury.

Signs and symptoms Discomfort in the chest. Corneal damage. Narcosis. Cyanosis (blue tissue condition, nails, lips, and/or skin). Coughing. Conjunctivitis. Defatting of the skin. Skin irritation.

3. Composition / Information on Ingredients

Components	CAS #	Percent
Diethylene Glycol Monobutyl Ether	112-34-5	8 - 10
2-Butoxyethanol	111-76-2	8 - 10
n-Butane	106-97-8	3 - 5
Propane	74-98-6	1 - 3
Non-hazardous and other components below reportable levels		60 - 80

4. First Aid Measures

First aid procedures

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

Skin contact Immediately flush skin with plenty of water. Remove and isolate contaminated clothing and shoes. Get medical attention immediately. Wash clothing separately before reuse.

Inhalation
Ingestion

Move to fresh air. Call a physician if symptoms develop or persist.
In the unlikely event of swallowing contact a physician or poison control center. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If ingestion of a large amount does occur, call a poison control center immediately.

5. Fire Fighting Measures

Flammable properties Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard.

Extinguishing media

Suitable extinguishing media Alcohol foam. Dry chemical. Carbon dioxide (CO₂).

Protection of firefighters

Protective equipment and precautions for firefighters In case of fire and/or explosion do not breathe fumes. Containers should be cooled with water to prevent vapor pressure build up.

6. Accidental Release Measures

Methods for containment Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk.

Methods for cleaning up Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

7. Handling and Storage

Handling Pressurized container: Do not pierce or burn, even after use. Do not smoke while using or until sprayed surface is thoroughly dry. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not re-use empty containers. Do not get this material in contact with eyes. Avoid contact with skin. Avoid prolonged exposure.

Storage Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Keep away from heat and flame. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Avoid exposure to long periods of sunlight. Keep out of the reach of children. Keep away from food, drink and animal feedingstuffs. Level 1 Aerosol (NFPA 30B)

8. Exposure Controls / Personal Protection

Exposure limits

ACGIH

Components	CAS #	TWA	STEL	Ceiling
Diethylene Glycol Monobutyl Ether	112-34-5	20 ppm	Not established	Not established
2-Butoxyethanol	111-76-2	20 ppm	Not established	Not established
n-Butane	106-97-8	1000 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established

OSHA

Components	CAS #	TWA	STEL	Ceiling
Diethylene Glycol Monobutyl Ether	112-34-5	100 ppm	Not established	Not established
2-Butoxyethanol	111-76-2	50 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established

Personal protective equipment

Eye / face protection Not normally needed. Chemical goggles are recommended. Do not get in eyes.

Skin protection Choose body protection according to the amount and concentration of the dangerous substance at the work place. Wear appropriate chemical resistant clothing. Chemical resistant gloves.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

9. Physical & Chemical Properties

Appearance	Compressed liquefied gas.
Boiling point	230 °F (110 °C) estimated
Color	Colorless.
Density	0.9421 g/cm ³ estimated
Flammability (HOC)	8.06 kJ/g estimated
Flash back	No
Flash point	-156 °F (-104.4 °C) estimated
Form	Aerosol.
Freezing point	Not available
Odor	Butyl
pH	11.5 - 12.5
Physical state	Liquid.
Pressure	50 - 60 psig @70F
Solubility	Completely
Specific gravity	0.9422 estimated

10. Chemical Stability & Reactivity Information

Chemical stability	Risk of ignition. Instability caused by elevated temperatures.
Conditions to avoid	Heat, flames and sparks.
Hazardous decomposition products	Irritants.

11. Toxicological Information

Acute effects	Acute LD50: 2322 mg/kg estimated, Rat, Dermal Acute LC50: 23 mg/l/4h estimated, Rat, Inhalation	
Component analysis - LD50	Toxicology Data - Selected LD50s and LC50s	
2-Butoxyethanol	111-76-2	Inhalation LC50 Rat 2.21 mg/L 4 h; Inhalation LC50 Rat 450 ppm 4 h; Oral LD50 Rat 470 mg/kg; Dermal LD50 Rat 2270 mg/kg; Dermal LD50 Rabbit 220 mg/kg
Diethylene Glycol Monobutyl Ether	112-34-5	Oral LD50 Rat 3384 mg/kg; Dermal LD50 Rabbit 2700 mg/kg
n-Butane	106-97-8	Inhalation LC50 Rat 658 mg/L 4 h
Propane	74-98-6	Inhalation LC50 Rat 658 mg/L 4 h

12. Ecological Information

Ecotoxicity	LC50 7225 mg/L, Fish, 96.00 Hours, EC50 12002 mg/L, Daphnia, 48.00 Hours, Contains a substance which causes risk of hazardous effects to the environment.
--------------------	---

13. Disposal Considerations

Waste codes	D001: Waste Flammable material with a flash point <140 F D002: Waste Corrosive material [pH <=2 or >=12.5, or corrosive to steel]
Disposal instructions	Contents under pressure. Dispose of this material and its container to hazardous or special waste collection point. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name	Consumer commodity
Hazard class	ORM-D
Subsidiary hazard class	None
Additional information:	
Packaging exceptions	156, 306
Packaging non bulk	156, 306
Packaging bulk	None

IMDG

Basic shipping requirements:

Proper shipping name	AEROSOLS
Hazard class	2.1
UN number	1950
Additional information:	
Packaging exceptions	LTD QTY
Item	5F
Labels required	None
Transport Category	2



IATA

Basic shipping requirements:

Proper shipping name	Aerosols, flammable
Hazard class	2.1
UN number	1950
Additional information:	
Packaging exceptions	LTD QTY
Labels required	2.1



15. Regulatory Information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

2-Butoxyethanol	111-76-2	1.0 % de minimis concentration (applies to R-(OCH ₂ CH ₂) _n -OR', where n = 1,2, or 3, R=alkyl C7 or less, or R = phenyl or alkyl substituted phenyl, R' = H or alkyl C7 or less, or OR' consisting of carboxylic acid ester, sulfate, phosphate, nitrate, or sulfonate, Chemical Category N230)
Diethylene Glycol Monobutyl Ether	112-34-5	1.0 % de minimis concentration (applies to R-(OCH ₂ CH ₂) _n -OR', where n = 1,2, or 3, R=alkyl C7 or less, or R = phenyl or alkyl substituted phenyl, R' = H or alkyl C7 or less, or OR' consisting of carboxylic acid ester, sulfate, phosphate, nitrate, or sulfonate, Chemical Category N230)

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical	Yes
-------------------------------------	-----

CERCLA (Superfund) reportable quantity

None

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely hazardous substance	No
Section 311 hazardous chemical	Yes
Hazard categories (311/312)	Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations**U.S. - Pennsylvania - RTK (Right to Know) List**

2-Butoxyethanol	111-76-2	Present
Diethylene Glycol Monobutyl Ether	112-34-5	Environmental hazard
n-Butane	106-97-8	Present
Propane	74-98-6	Present

16. Other Information

Further information

HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings

Health: 1
 Flammability: 2
 Physical hazard: 0

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and experience currently available.

MSDS sections updated

Product and Company Identification: Product and Company Identification

Prepared by

Regulatory Compliance