

MATERIAL SAFETY 3M
 DATA SHEET 3M Center
 St. Paul, Minnesota
 55144-1000
 1-800-364-3577 or (651) 737-6501 (24 hours)

Copyright, 2001, Minnesota Mining and Manufacturing Company.
 All rights reserved. Copying and/or downloading of this
 information for the purpose of properly utilizing 3M products
 is allowed provided that:

- 1) the information is copied in full with no changes unless
 prior agreement is obtained from 3M, and
- 2) neither the copy nor the original is resold or otherwise
 distributed with the intention of earning a profit thereon.

DIVISION: AUTOMOTIVE AFTERMARKET
 TRADE NAME:

3M(TM) Plastic and Emblem Adhesive - Clear, P.N. 08061
 ID NUMBER/U.P.C. :
 60-9800-2706-8 00-51135-08061-0 60-9800-3750-5 00-51131-34021-3
 62-4475-2609-6 00-51135-08061-0
 ISSUED: March 27, 2001
 SUPERSEDES: August 04, 2000
 DOCUMENT: 10-4794-3

1. INGREDIENT	C.A.S. NO.	PERCENT
Methyl Ethyl Ketone.....	78-93-3	30.0 - 60.0
Vinyl Chloride-Vinyl Acetate-Maleic Acid Polymer.....	9005-09-8	10.0 - 30.0
Adipic acid-1,4-butanediol-MDI- neopentyl glycol copolymer.....	56815-45-3	10.0 - 30.0
4,4'-ISOPROPYLIDENEDIPHENOL- EPICHLOROHYDRIN POLYMER.....	25068-38-6	0.1 - 1.0
Isopropyl Alcohol.....	67-63-0	< 0.2

The components of this product are in compliance with the chemical
 notification requirements of TSCA.

This product contains the following toxic chemical or chemicals subject to
 the reporting requirements of Section 313 of Title III of the Emergency
 Planning and Community Right-To-Know Act of 1986 and 40 CFR Part 372:

Methyl Ethyl Ketone

2. PHYSICAL DATA

BOILING POINT:..... 176.00 F
 (MEK)
 VAPOR PRESSURE:..... 80.0000 mmHg
 @ 68F
 VAPOR DENSITY:..... 2.50 Air=1
 EVAPORATION RATE:..... 2.70 Ether=1
 SOLUBILITY IN WATER:..... Very slight

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

2. PHYSICAL DATA (continued)

SPECIFIC GRAVITY:..... 0.950 Water=1
PERCENT VOLATILE:..... ca. 60 % by wt
pH:..... N/D
VISCOSITY:..... ca. 8500.0 centipoise
MELTING POINT:..... N/D

APPEARANCE AND ODOR:

Liquid, clear, ketone odor

3. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:..... 20.00 F TCC
(methyl ethyl ketone)
FLAMMABLE LIMITS - LEL:..... 1.80 % by vol
FLAMMABLE LIMITS - UEL:..... 11.50 % by vol
AUTOIGNITION TEMPERATURE:..... N/D

EXTINGUISHING MEDIA:

Carbon dioxide, Dry chemical, Foam

SPECIAL FIRE FIGHTING PROCEDURES:

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back.

NFPA HAZARD CODES: HEALTH: 2 FIRE: 3 REACTIVITY: 0
UNUSUAL REACTION HAZARD: none

OSHA FIRE HAZARD CLASS: Class IB Flammable Liquid

4. REACTIVITY DATA

STABILITY: Stable

INCOMPATIBILITY - MATERIALS/CONDITIONS TO AVOID:

Not applicable.

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

4. REACTIVITY DATA (continued)

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon Monoxide and Carbon Dioxide, Toxic Vapors, Gases or
Particulates.

5. ENVIRONMENTAL INFORMATION

SPILL RESPONSE:

Refer to other sections of this MSDS for information regarding
physical and health hazards, respiratory protection, ventilation, and
personal protective equipment. Ventilate area. Extinguish all
ignition sources. Contain spill. Evacuate unprotected personnel
from hazard area. Cover with inorganic absorbent material. Collect
using non-sparking tools. Clean up residue with an appropriate
organic solvent. Read and follow safety precautions on the solvent
label and MSDS. Place in metal container. Seal the container.

RECOMMENDED DISPOSAL:

Dispose of according to the policies/procedures contained in the 3M
Waste Management Program Manual and the instructions provided on the
Waste Stream Profile Reference Sheet. Consult your Waste Management
(RCRA) Coordinator with any questions.

ENVIRONMENTAL DATA:

Not determined.

REGULATORY INFORMATION:

Volatile Organic Compounds: 568 gms/liter South Coast Air Quality Mgmt
Dist Method Rule 443.1, calculated.
VOC Less H2O & Exempt Solvents: 568 gms/liter South Coast Air Quality Mgmt
Dist Method Rule 443.1, calculated.

Since regulations vary, consult applicable regulations or authorities
before disposal. U.S. EPA Hazardous Waste Number = D001 (Ignitable)
D035 (Methyl ethyl ketone) D043 (Vinyl chloride)

EPCRA HAZARD CLASS:

FIRE HAZARD: Yes PRESSURE: No REACTIVITY: No ACUTE: Yes CHRONIC: No

6. SUGGESTED FIRST AID

EYE CONTACT:

Immediately flush eyes with large amounts of water. Get immediate
medical attention.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

6. SUGGESTED FIRST AID (continued)

SKIN CONTACT:

Immediately wash skin with soap and large amounts of water. Remove contaminated clothing. If signs/symptoms occur, call a physician. Wash contaminated clothing before reuse and dispose of contaminated shoes. Destroy or properly dispose of contaminated shoes.

INHALATION:

Remove person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, get immediate medical attention.

IF SWALLOWED:

Do not induce vomiting. Drink two glasses of water. Call a physician.

7. PRECAUTIONARY INFORMATION

EYE PROTECTION:

Avoid eye contact. Wear vented goggles. Wear safety glasses with side shields.

SKIN PROTECTION:

Avoid skin contact. Wear appropriate gloves when handling this material. A pair of gloves made from the following material(s) are recommended: butyl rubber, polyethylene/ethylene vinyl alcohol.

RECOMMENDED VENTILATION:

Do not use in a confined area or areas with little or no air movement. Use in a well-ventilated area. Provide sufficient ventilation to maintain emissions below recommended exposure limits. If exhaust ventilation is not adequate, use appropriate respiratory protection.

RESPIRATORY PROTECTION:

Avoid breathing of vapors. Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: half-mask organic vapor respirator, full-face organic vapor respirator.

PREVENTION OF ACCIDENTAL INGESTION:

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Wash hands after handling and before eating. Do not ingest.

RECOMMENDED STORAGE:

Store away from heat. Keep container closed when not in use. Keep out of the reach of children.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

7. PRECAUTIONARY INFORMATION (continued)

FIRE AND EXPLOSION AVOIDANCE:

Keep container tightly closed. Keep away from heat, sparks, open flame, and other sources of ignition. Prevent all sources of ignition. Extremely flammable liquid and vapor. Ground containers securely when transferring contents. Wear low static or properly grounded shoes. No smoking while handling this material. Avoid static discharge.

EXPOSURE LIMITS

INGREDIENT	VALUE	UNIT	TYPE	AUTH	SKIN*
Methyl Ethyl Ketone.....	200	PPM	TWA	OSHA	
Methyl Ethyl Ketone.....	300	PPM	STEL	OSHA	
Methyl Ethyl Ketone.....	200	PPM	TWA	ACGIH	
Methyl Ethyl Ketone.....	300	PPM	STEL	ACGIH	
Vinyl Chloride-Vinyl Acetate- Maleic Acid Polymer.....	NONE	NONE	NONE	NONE	
Adipic acid-1,4-butanediol-MDI- neopentyl glycol copolymer.....	NONE	NONE	NONE	NONE	
4,4'-ISOPROPYLIDENEDIPHENOL- EPICHLOROHYDRIN POLYMER.....	NONE	NONE	NONE	NONE	
Isopropyl Alcohol.....	400	PPM	TWA	ACGIH	
Isopropyl Alcohol.....	500	PPM	STEL	ACGIH	
Isopropyl Alcohol.....	400	PPM	TWA	OSHA	
Isopropyl Alcohol.....	500	PPM	STEL	OSHA	

* SKIN NOTATION: Listed substances indicated with 'Y' under SKIN refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

SOURCE OF EXPOSURE LIMIT DATA:

- ACGIH: American Conference of Governmental Industrial Hygienists
- OSHA: Occupational Safety and Health Administration
- NONE: None Established

8. HEALTH HAZARD DATA

EYE CONTACT:

Moderate Eye Irritation: signs/symptoms can include redness, swelling, pain, tearing, and hazy vision.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

8. HEALTH HAZARD DATA (continued)

SKIN CONTACT:

Moderate Skin Irritation (after prolonged or repeated contact):
signs/symptoms can include redness, swelling, itching, and dryness.

Prolonged or repeated exposure may cause:

Allergic Skin Reaction: signs/symptoms can include redness,
swelling, blistering, and itching.

INHALATION:

May be harmful if inhaled.

Intentional concentration and inhalation may be harmful or fatal.

Irritation (upper respiratory): signs/symptoms can include soreness
of the nose and throat, coughing and sneezing.

Prolonged or repeated overexposure, above recommended guidelines, may
cause:

Central Nervous System Depression: signs/symptoms can include
headache, dizziness, drowsiness, incoordination, slowed reaction
time, slurred speech, giddiness and unconsciousness.

WHILE THE FOLLOWING EFFECTS ARE ASSOCIATED WITH ONE OR MORE OF THE
INDIVIDUAL INGREDIENTS IN THIS PRODUCT AND ARE REQUIRED TO BE
INCLUDED ON THE MSDS BY THE U.S. OSHA HAZARD COMMUNICATION STANDARD,
THEY ARE NOT EXPECTED EFFECTS DURING FORESEEABLE USE OF THIS PRODUCT.

Prolonged or repeated overexposure, above recommended guidelines, may
cause:

Liver Effects: signs/symptoms can include yellow skin(jaundice)
and tenderness of upper abdomen.

IF SWALLOWED:

Ingestion may cause:

Irritation of Gastrointestinal Tissues: signs/symptoms can
include pain, vomiting, abdominal tenderness, nausea, blood in
vomitus, and blood in feces.

Central Nervous System Depression: signs/symptoms can include
headache, dizziness, drowsiness, muscular weakness,
incoordination, slowed reaction time, fatigue, blurred vision,
slurred speech, giddiness, tremors and convulsions.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

SECTION CHANGE DATES

INGREDIENTS	SECTION CHANGED SINCE August 04, 2000	ISSUE
ENVIRONMENTAL INFO.	SECTION CHANGED SINCE August 04, 2000	ISSUE
SUGG. FIRST AID	SECTION CHANGED SINCE August 04, 2000	ISSUE
PRECAUTIONARY INFO.	SECTION CHANGED SINCE August 04, 2000	ISSUE
HEALTH HAZARD DATA	SECTION CHANGED SINCE August 04, 2000	ISSUE

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.