

MATERIAL SAFETY DATA SHEET



Date-Issued: 04/20/2005
MSDS Ref. No: 10098
Date-Revised: 05/17/2005
Revision No: New MSDS

XP Renew-It™

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: XP Renew-It™
GENERAL USE: Automotive reconditioning product
PRODUCT DESCRIPTION: Silicone based Lotion
PRODUCT CODE: 98
PRODUCT FORMULATION NAME: XP Renew-It™
CHEMICAL FAMILY: none
GENERIC NAME: Silicone Based Lotion

MANUFACTURER

Auto Wax Company, Inc.
Auto Magic®
1275 Round Table Drive
Dallas, TX 75247
Product Stewardship: 1-214-631-4000
Transportation: 1-800-826-0828
Auto Wax Company, Inc.
Auto Magic®

24 HR. EMERGENCY TELEPHONE NUMBERS

1-800-826-0828

2. COMPOSITION / INFORMATION ON INGREDIENTS

<u>Chemical Name</u>	<u>Wt.%</u>	<u>CAS#</u>	<u>EINECS#</u>
Distillates (petroleum) hydrotreated light	10 - 15	64742-47-8	265-149-8
Naphtha(petroleum), hydrotreated heavy (mineral spirits)	1 - 3	64742-48-9	265-150-3

COMMENTS: Product composition ranges shown are typical values for health, safety and environmental use and are not intended as specification.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS: Harmful if swallowed.

POTENTIAL HEALTH EFFECTS

EYES: Moderately irritating to the eyes.

SKIN: Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

SKIN ABSORPTION: not established

INGESTION: Harmful if swallowed.

INHALATION: Prolonged or excessive inhalation may cause respiratory tract irritation.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Eye contact may cause redness, tearing and a burning sensation.

SKIN ABSORPTION: not established

ACUTE TOXICITY: May cause headaches and dizziness.

CHRONIC: not available

MEDICAL CONDITIONS AGGRAVATED: dermatitis may be aggravated by excessive exposure to skin.

ROUTES OF ENTRY: include skin contact, eye contact and ingestion

TARGET ORGAN STATEMENT: not established

CANCER STATEMENT: not established

4. FIRST AID MEASURES

EYES: Flush eye with water for 15 minutes. Seek medical attention if irritation persists.

SKIN: Wash with soap and water.

INGESTION: Do not induce vomiting. Seek medical attention immediately.

INHALATION: Move to fresh air

5. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: ~ 54°C TCC

FLAMMABLE LIMITS: not available

FLAMMABLE CLASS: Material will not support combustion.

EXTINGUISHING MEDIA: use foam, dry chemical or carbon dioxide extinguisher

HAZARDOUS COMBUSTION PRODUCTS: Carbon Monoxide and Carbon Dioxide

EXPLOSION HAZARDS: not established

FIRE FIGHTING PROCEDURES: not established

AUTOIGNITION TEMPERATURE: not established

SENSITIVE TO STATIC DISCHARGE: none expected

SENSITIVITY TO IMPACT: none expected

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Contain and collect with absorbent

LARGE SPILL: LARGE SPILLS: Shut off leak if safe to do so. Contain material to avoid run off and collect spill with absorbent.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Avoid runoff into storm sewers and ditches which lead to waterways.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Keep out of reach of Children.

STORAGE TEMPERATURE: 4°C (40°F) minimum to 35°C (95°F) maximum

SHELF LIFE: one year

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES:

OSHA HAZARDOUS COMPONENTS (29 CFR 1910.1200)

EXPOSURE LIMITS

Chemical Name**OSHA PEL****ACGIH TLV****Supplier OEL**

Distillates (petroleum) hydrotreated light

TWA

300 ppm 2300 mg/m³

Naphtha(petroleum), hydrotreated heavy (mineral spirits)

TWA

300 ppm 1900 mg/m³**ENGINEERING CONTROLS:** Good general ventilation should be sufficient to control airborne levels.**PERSONAL PROTECTIVE EQUIPMENT****EYES AND FACE:** Wear safety glasses with side shields or goggles.**SKIN:** Use Nitrile/ Vinyl gloves**RESPIRATORY:** NIOSH respirator -(organic vapor) in absence of proper environmental control.**PROTECTIVE CLOTHING:** Clean, body-covering clothing**9. PHYSICAL AND CHEMICAL PROPERTIES****PHYSICAL STATE:** Liquid**ODOR:** Characteristic**APPEARANCE:** White Liquid**COLOR:** White**pH:** ~ 8.5 to 9.5**PERCENT VOLATILE:** Not Available**VAPOR PRESSURE:** Not Available**VAPOR DENSITY:** Not Available**FREEZING POINT:** ~ (32°F)**SOLUBILITY IN WATER:** Mixable**SPECIFIC GRAVITY:** ~ 0.93 at 25°C**(VOC):** ~ 3 % by weight**10. STABILITY AND REACTIVITY****STABLE:** YES**HAZARDOUS POLYMERIZATION:** NO**11. TOXICOLOGICAL INFORMATION****SENSITIZATION:** not available

CARCINOGENICITY:

IARC: Listed by IARC- NO

NTP: Listed by NTP- NO

OSHA: Listed by OSHA- NO

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: not available

ECOTOXICOLOGICAL INFORMATION: not available

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose in accordance with local, state, and federal laws.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

OTHER SHIPPING INFORMATION: Refer to bill of lading or container label for DOT or other transportation hazard classification, if any.

15. REGULATORY INFORMATION

CANADA

WHMIS HAZARD SYMBOL AND CLASSIFICATION



WHMIS Combustible Liquid



WHMIS Toxic

16. OTHER INFORMATION

PREPARED BY: Mark Dean

REVISION SUMMARY New MSDS

HMIS RATING

NFPA CODES

HEALTH:	-	1
FLAMMABILITY:		2
PHYSICAL HAZARD:		0
PERSONAL PROTECTION:		

0

MANUFACTURER DISCLAIMER: The information in this MSDS was obtained from current and reputable sources. However, the data is provided without any warranty, express or implied, regarding its correctness or accuracy. It is the user's responsibility both to determine safe conditions for use of this product and to assume liability for loss, injury, damage or expense resulting from improper use of this product.