

MALCO[®] EPIC[®] PRO CERAMIC COATING (#109330)

DESCRIPTION

EPIC[®] PRO Ceramic Coating is designed to produce the ultimate vehicle finish. This specially formulated coating provides 3 years (or 36,000 miles) of protection, along with the industry's highest gloss finish. It bonds with the clear coat to create a durable, hydrophobic surface that prevents dirt, water spots, and other contaminants from adhering to paint. Apply EPIC PRO Ceramic Coating to your vehicle for the ultimate "wet" look. The optimum viscosity of this unique formula simplifies application. However, professional installation of EPIC PRO Ceramic Coating and the EPIC[®] Ceramic Coating System is recommended.

DIRECTIONS

EPIC PRO Ceramic Coating requires a clean, smooth surface for proper adhesion. Wash, clay bar, and machine polish your vehicle prior to application. We recommend washing with EPIC[®] Ceramic Prep Wash Concentrate and correcting paint imperfections with the EPIC[®] Paint Correction System. If you cannot achieve a professional level of cleaning and paint correction on your own, please seek professional help. Ensure the vehicle is at room temperature (50°F - 75°F). Only apply the product in a covered, dust-free garage and allow the vehicle to remain inside for at least 24 hours afterward. For maximum results:

- Put on a pair of rubber gloves for protection. Shake product well prior to use.
- Clean and prep your surface with EPIC[®] Ceramic Final Prep Wipe, using a lint-free cloth.
- Wrap a Suede Cloth around the Applicator Pad. Apply 3-4 drops of EPIC PRO Ceramic Coating to the cloth, and immediately reseal the product.
- Apply coating to surface in a crosshatch pattern, using even pressure. We recommend working in a defined 20-in x 20-in area until the product is worked into the clear coat.
- Expect the coated area to rainbow or flash within 30-90 seconds of application. At this point, begin removing the product with a clean, microfiber towel. Be sure to remove any remaining residue.
- Repeat steps for coating the entire vehicle, using an overlapping technique on each section to ensure full coverage.
- Keep the vehicle in a controlled environment for at least 12 hours while keeping it dry for a minimum of 24 hours. Complete bonding with the paint can take up to seven days, so it is vital to have garage access.

FEATURES AND BENEFITS

| | |
|--|--|
| Easy-to-apply coating | Bonds with the clear coat for outstanding depth of gloss |
| Designed to complete the EPIC Paint Correction and Protection System | Optimum viscosity simplifies application for experts and novices alike |
| Produces the ultimate “wet” look | Excellent hydrophobic properties allow water and dirt to slide right off |

PACKAGE CONTENTS

EPIC[®] PRO Ceramic Single Use Kit (#109330)

1 fl. oz EPIC PRO Ceramic Coating
1 Technical Data Sheet
1 Applicator Pad
10 Suede cloths

PRODUCT FAQs

Q1: What should I use to apply EPIC PRO Ceramic Coating?

A1: The suede cloth should always be used for application. These clothes are designed for one use only and should be disposed of after application.

Q2: How long does it take to apply EPIC PRO Ceramic Coating?

A2: It depends on the level of paint correction required prior to application and the experience level of the installer. It is important not to rush application. A few hours can be typical.

Q3: Is one layer of coating enough to provide protection?

A3: Yes, one layer is enough. However, multiple layers of ceramic coating will not harm your vehicle and will only provide extended durability.

Q4: How do I know when the coating is completely worked into the clearcoat?

A4: Work the product into the vehicle surface in a crosshatch pattern until you can no longer see any remaining product. You will feel a slight resistance building as the coating is fully worked in.