Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 07/20/2010 Reviewed on 07/20/2010

1 Identification of substance

Trade name: **GLOSS WHITE ENAMEL**

Product codes: ZB00980002 Manufacturer/Supplier: Hi-Tech Industries

19270 West Eight Mile Road Southfield, MI 48075

Health & Safety Department Information department: **Emergency information:** INFOTRAC 1-800-535-5053

2 Composition/Data on components

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous	components:	
	Acetone	21.25%
74-98-6	propane	18.83%
108-88-3		11.67%
64742-89-8	VM&P Naphtha	11.25%
106-97-8		11.06%
64742-47-8	Mineral Spirits	4.92%
67-63-0	isopropyl alcohol	2.35%

Additional information: For the wording of the listed risk phrases refer to section 3.

3 Hazards identification

Hazard description:



Harmful

Extremely flammable

Physical dangers: Extremely flammable liquid and vapor in a pressurized container. Keep away from heat, sparks, and

flame.

Has narcotizing effect. Extremely flammable.

Irritating to eyes.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Do not spray on a naked flame or any incandescent material. Buildup of explosive mixtures possible without sufficient ventilation.

Effects of chronic

overexposure:

May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be

harmful or fatal.

NFPA ratings (0 - 4):

Health = Fire = Reactivity = 3

HMIS-ratings (0 - 4):

Health= Fire= Physical Hazard= 3

4 First aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact: Move to fresh air. Rinse opened eye for several minutes under running water. If symptoms persist, consult

a doctor.

After swallowing: Contact physician or poison control center.

5 Fire fighting measures

Extinguishing agents: CO2, sand, extinguishing powder. Do not use water.

CO2, sand, extinguishing powder, or water spray. Fight larger fires with water spray or alcohol resistant

foam.

Protective equipment: No special measures required.

6 Accidental release measures

Wear protective equipment. Keep unprotected persons away. Personal safety:

Inform appropriate authorities in case of seepage into water course or sewage system. **Environmental safety:**

Do not allow product to reach sewage systems or ground water.

Do not flush with water or aqueous cleansing agents. Use diluted caustic solution. Soak up spills with inert absorbent material. Refer to section 13 for disposal information. Clean-up/collection:

Ensure adequate ventilation.

7 Handling and storage

Fire/explosion protection: Do not smoke. Protect from electrostatic charges.

Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic

discharges.

(Contd. on page 2)

Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 07/20/2010 Reviewed on 07/20/2010

Trade name: GLOSS WHITE ENAMEL

(Contd. of page 1)

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Observe pressurized container storage regulations. Consult with your local authorities. Storage requirements:

8 Exposure controls and personal protection:

Components with limit values that require monitoring at the workplace:

67-64-1 Acetone

PEL 2400 mg/m³, 1000 ppm REL 590 mg/m³, 250 ppm

Short-term value: 1782 mg/m³, 750 ppm Long-term value: 1188 mg/m³, 500 ppm

74-98-6 propane

PEL 1800 mg/m³, 1000 ppm REL 1800 mg/m³, 1000 ppm TLV Varies mg/m³, 1000 ppm

108-88-3 Toluene

PEL Short-term value: C 300; 500* ppm Long-term value: 200 ppm

*10-min peak per 8-hr shift Short-term value: 560 mg/m³, 150 ppm REL Long-term value: 375 mg/m³, 100 ppm

75 mg/m³, 20 ppm NIC-BEI

106-97-8 n-butane

REL 1900 mg/m³, 800 ppm TLV Varies mg/m³, 1000 ppm TLV

67-63-0 isopropyl alcohol

PEL 980 mg/m³, 400 ppm

Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm REL Short-term value: 984 mg/m³, 400 ppm TLV Long-term value: 492 mg/m³, 200 ppm BEI

Hygienic protection:

Keep away from foodstuffs and animal feed. Wash hands after use.

Breathing equipment:

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you

suspect overexposure conditions exist, please consult an authority on chemical hygeine.

Protective gloves. The glove material has to be impermeable and resistant to the substance. No glove recommendation can be given. Hand protection:

Eye protection: Tightly sealed goggles

9 Physical and chemical properties:

General Information:

Form: Aerosol

Color: According to trade name description in section 1.

Odor: Aromatic -44°C (-47°F) **Boiling point:** Flash point: -19°C (-2°F)

Auto igniting: Product is not self-igniting.

Danger of explosion: Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120

degrees fahrenheit.

In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.5 Vol % Upper Explosion Limit: 10.9 Vol % Vapor Pressure: 40 PSI, 2750 hPa

Density at 20°C (68°F): 0.75 g/cm³

Between 0.77 and 0.85 (Water equals 1.00) Specific Gravity:

VOC content: 568.9 g/l / 4.75 lb/gl

VOC content (less exempt solvents): 60.6 % MIR Value: 1.07 Solids content: 17.9 %

10 Stability and reactivity:

Conditions to avoid: Do not allow the can to exceed 120 degrees Fahrenheit. Stable at normal temperatures.

(Contd. of page 2)

Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 07/20/2010 Reviewed on 07/20/2010

Trade name: GLOSS WHITE ENAMEL

Materials to be avoided:

No dangerous reactions known. **Hazardous Reactions:**

11 Toxicological information:

Skin effects: No irritant effect. Eye effects: Irritating effect.

No sensitizing effects known. Sensitization:

Additional toxicological

information: Harmful

12 Ecological information

Other information: Product does not contain CFC's.

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), or chlorinated solvents.

Aquatic toxicity: Hazardous for water, do not empty into drains.

13 Disposal considerations

DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty can's should be recycled.

14 Transport information:

Hazard class: Identification number: N/A Label 2.1

ADR/RID/TDG class: 5F Gases

UN-Number: 1950 **IMDG Class:** 2.1 Packaging group: **EMS Number:** F-D,S-U Marine pollutant: No ICAO/IATA Class: 2.1

Proper shipping name: Aerosols, Flammable

Consumer Commodity ORM-D

15 Regulations

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-88-3 Toluene

67-63-0 isopropyl alcohol

TSCA: All ingredients are listed.

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

100-41-4 ethyl benzene

California Proposition 65 chemicals known to cause

developmental toxicity: 108-88-3 Toluene

CANADIAN ENVIRONMENTAL

Canada:

PROTECTION ACT: WHMIS Symbols for

- Compressed gas

- Very toxic material causing other toxic effects

EPA: A= Known human carcinogen B= Probable human carcinogen

C= Possible human carcinogen

D= Not classifiable as to human carcinogenicity: Inadequate human and animal evidence of carcinogenicity (or no data is available).

All hazardous ingredients for this product appear on the Canadian Domestice Substance List.

'Data are inadequate for an assessment of human carcinogeni potential.'

'Inadequate information to assess carcinogenic potential.'

67-64-1	Acetone	I
108-88-3	Toluene	Ш

IARC: Group 2A: The ingredient is probably carcinogenic to humans.

Group 2B: The ingredient is possibly carcinogenic to humans. There is limited evidence of carcinogenicity.

(Contd. on page 4)

Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 07/20/2010 Reviewed on 07/20/2010

Trade name: GLOSS WHITE ENAMEL

Group 3: The ingredient is unclassifiable as to its carcinogenicity to humans.

(Contd. of page 3)

108-88-3	Toluene	3]
13463-67-7	titanium dioxide	2B	1
67-63-0	isopropyl alcohol	3	1

ACGIH:

A1-designates a confirmed human carcinogen. A2-designates a suspected human carcinogen.

A3-designates an animal carcinogen.

	A4-designates not classifiable as a numan carcinogen.	
67-64-1	Acetone	A4
108-88-3	Toluene	A4
13463-67-7	titanium dioxide	A4
67-63-0	isopropyl alcohol	A4

NIOSH:

13463-67-7 titanium dioxide

Risk phrases: Extremely flammable.

Irritating to eyes.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Safety phrases: Keep out of the reach of children.

Keep away from sources of ignition - No smoking.

Do not breathe gas/fumes/vapour/spray

Do not empty into drains, dispose of this material and its container at hazardous or special waste

collection point

Wear suitable protective clothing and gloves.

If swallowed, seek medical advice immediately and show this container or label.

Use only in well-ventilated areas.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Regulatory Affairs Contact:

Abbreviations and

acronyms:

IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO) PP: Severe Marine Pollutant

PP: Severe Marine Pollutant
P: Marine Pollutant
P: Marine Pollutant
P: Marine Pollutant
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
ISO: International Organization for Standardization
EPA: Environmental Protection Agency
IARC: International Agency for the Research of Cancer
NIOSH: National Institute for Occupational Safety and Health
TSCA: Toxic Substances Control Act
CPSC: Consumer Product Safety Commission

USA