

Safety Data Sheet

Copyright, 2018 Meguiar's, Inc.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Meguiar's, Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 38-3347-2
 Version Number:
 1.03

 Issue Date:
 12/06/18
 Supercedes Date:
 10/09/18

SECTION 1: Identification

1.1. Product identifier

D180101 & D180105, Wheel & Paint Iron DECON (29-46C)

Product Identification Numbers

LB-1100-2635-4, LB-1100-2635-5, 14-1001-1950-3, 14-1001-1951-1

1.2. Recommended use and restrictions on use

Recommended use

Automotive

1.3. Supplier's details

MANUFACTURER: Meguiar's, Inc. DIVISION: Meguiar's

ADDRESS: 17991 Mitchell South, Irvine, CA 92614, USA

Telephone: 949-752-8000 (Fax: 949-752-5784)

1.4. Emergency telephone number

CHEMTREC 1-800-424-9300 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification

Acute Toxicity (oral): Category 4.

Serious Eye Damage/Irritation: Category 2A.

Skin Sensitizer: Category 1.

2.2. Label elements

Signal word

Warning

Symbols

Exclamation mark |

Pictograms



Hazard Statements Harmful

if swallowed. Causes serious eye irritation.

May cause an allergic skin reaction.

Precautionary Statements

General:

Keep out of reach of children.

Prevention:

Avoid breathing dust/fume/gas/mist/vapors/spray.

Wear protective gloves and eye/face protection.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Rinse mouth.

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2% of the mixture consists of ingredients of unknown acute oral toxicity.

14% of the mixture consists of ingredients of unknown acute dermal toxicity.

17% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Water	7732-18-5	60 - 100 Trade Secret *
Acetic acid, mercapto-, monoammonium salt	5421-46-5	10 - 30 Trade Secret *
Diethylene Glycol Monoethyl Ether	111-90-0	1 - 5 Trade Secret *
Sodium Xylene Sulfonate	1300-72-7	1 - 5 Trade Secret *
Fatty Alcohol Ether Sulfate	Trade Secret*	< 3 Trade Secret *
2-Butoxyethanol	111-76-2	0.5 - 1.5 Trade Secret *
Sodium Mono-C10-16-Alkyl Sulfates	68585-47-7	0.5 - 1.5 Trade Secret *

D180101 & D180105, Wheel & Paint Iron DECON (29-46C)

12/06/18

Any remaining components do not contribute to the hazards of this material.

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance Condition Carbon monoxide **During Combustion** Carbon dioxide **During Combustion**

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

12/06/18

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

for the component.				
Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
2-Butoxyethanol	111-76-2	ACGIH	TWA:20 ppm	A3: Confirmed animal
				carcin.
2-Butoxyethanol	111-76-2	OSHA	TWA:240 mg/m3(50 ppm)	SKIN
Diethylene Glycol Monoethyl	111-90-0	AIHA	TWA:140 mg/m3(25 ppm)	
Ether				
THIOGLYCOLLIC ACID AND	5421-46-5	ACGIH	TWA:1 ppm	SKIN; Dermal sensitizer
ITS SALTS				

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

12/06/18

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form: Liquid

Odor, Color, Grade: Sulfurous Odor, Orange/Red, Liquid

Odor threshold No Data Available

pH 6.3 - 7

Melting point No Data Available

Boiling Point 212 °F

Flash Point Flash point > 93 °C (200 °F)

Evaporation rateNo Data AvailableFlammability (solid, gas)Not ApplicableFlammable Limits(LEL)No Data AvailableFlammable Limits(UEL)No Data AvailableVapor PressureNo Data AvailableVapor DensityNo Data Available

Density 1.05 g/cm³

Specific Gravity 1.05 [Ref Std:WATER=1]

Solubility in Water Complete

Solubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNo Data AvailableDecomposition temperatureNo Data AvailableViscosity20 - 80 centipoiseMolecular weightNo Data Available

Volatile Organic Compounds 1.3 % weight [*Test Method:*calculated per CARB title 2]

Percent volatile 77.5 % weight [*Test Method:* Estimated]

VOC Less H2O & Exempt Solvents 196 g/l [Test Method:calculated SCAQMD rule 443.1]

Page 5 of

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Light

10.5. Incompatible materials

Strong acids

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Harmful if swallowed. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Page 6 of 12

D180101 & D180105, Wheel & Paint Iron DECON (29-46C)

12/06/18

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation- Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE300 - 2,000 mg/kg
Diethylene Glycol Monoethyl Ether	Dermal	Rabbit	LD50 9,143 mg/kg
Diethylene Glycol Monoethyl Ether	Ingestion	Rat	LD50 5,400 mg/kg
Sodium Xylene Sulfonate	Dermal		LD50 estimated to be > 5,000 mg/kg
Sodium Xylene Sulfonate	Ingestion	Rat	LD50 > 5,000 mg/kg
Sodium Mono-C10-16-Alkyl Sulfates	Dermal	Rat	LD50 > 2,000 mg/kg
Sodium Mono-C10-16-Alkyl Sulfates	Ingestion	Rat	LD50 977 mg/kg
2-Butoxvethanol	Dermal	Guinea pig	LD50 > 2.000 mg/kg
2-Butoxyethanol	Inhalation- Vapor (4 hours)	Guinea pig	LC50 > 2.6 mg/l
2-Butoxyethanol	Ingestion	Guinea pig	LD50 1,414 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value	
Diethylene Glycol Monoethyl Ether	Rabbit	No significant irritation	
Sodium Mono-C10-16-Alkyl Sulfates	Rabbit	Irritant	
2-Butoxyethanol	Rabbit	Irritant	

Serious Eve Damage/Irritation

Name	Species	Value	
Diethylene Glycol Monoethyl Ether	Rabbit	Moderate irritant	
Sodium Mono-C10-16-Alkyl Sulfates	Rabbit	Corrosive	
2-Butoxyethanol	Rabbit	Severe irritant	

Skin Sensitization

Name	Species	Value
Diethylene Glycol Monoethyl Ether	Human	Not classified
2-Butoxyethanol	Guinea pig	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Diethylene Glycol Monoethyl Ether	In Vitro	Not mutagenic
Diethylene Glycol Monoethyl Ether	In vivo	Not mutagenic
2-Butoxyethanol	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

caremogenety							
Name	Robutation	S/helcipse	Value positive data exist, but the data are not				
2-Butoxyethanol		animal	sufficient for classification				
		species					

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Diethylene Glycol Monoethyl Ether	Dermal	Not classified for development	Rat	NOAEL 5,500 mg/kg/day	during organogenesis
Diethylene Glycol Monoethyl Ether	Ingestion	Not classified for development	Mouse	NOAEL 5,	during organogenesis
Diethylene Glycol Monoethyl Ether	Inhalation	Not classified for development	Rat	NOAEL 0.6 mg/l	during organogenesis
Diethylene Glycol Monoethyl Ether	Ingestion	Not classified for male reproduction	Rat	NOAEL 2,200 mg/kg/day	2 generation

D180101 & D180105, Wheel & Paint Iron DECON (29-46C) 12/06/18

2-Butoxyethanol	Dermal	Not classified for development	Rat	NOAEL 1,760	during
				mg/kg/day	gestation
2-Butoxyethanol	Ingestion	Not classified for development	Rat	NOAEL 100 mg/kg/day	during organogenesis
2-Butoxyethanol	Inhalation	Not classified for development	Multiple animal species		during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Diethylene Glycol Monoethyl Ether	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for		NOAEL Not available	
Sodium Mono- C10-16- Alkyl Sulfates	Inhalation	respiratory irritation	May cause respiratory irritation	similar health hazards	NOAEL Not available	
2-Butoxyethanol	Dermal	endocrine system	Not classified	Rabbit	NOAEL 902 mg/kg	6 hours
2-Butoxyethanol	Dermal	liver	Not classified	Rabbit	LOAEL 72 mg/kg	not available
2-Butoxyethanol	Dermal	kidney and/or bladder	Not classified	Rabbit	LOAEL 451 mg/kg	6 hours
2-Butoxyethanol	Dermal	blood	Not classified	Multiple animal species	NOAEL Not available	
2-Butoxyethanol	Inhalation	central nervous system depression	May cause drowsiness or	Human	NOAEL Not available	
2-Butoxyethanol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for	Human	NOAEL Not available	
2-Butoxyethanol	Inhalation	blood	Not classified	Multiple animal species	NOAEL Not available	
2-Butoxyethanol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
2-Butoxyethanol	Ingestion	blood	Not classified	Multiple animal species	NOAEL Not available	
2-Butoxyethanol	Ingestion	kidney and/or bladder	Not classified	Human	NOAEL Not available	Poisoning and/or abuse

Page 8 **of** 12

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Diethylene Glycol Monoethyl Ether	Dermal	kidney and/or bladder	Not classified	Rabbit	NOAEL 1,000 mg/kg/day	12 weeks
Diethylene Glycol Monoethyl Ether	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Pig	NOAEL 167 mg/kg/day	90 days
Diethylene Glycol Monoethyl Ether	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 2,700 mg/kg/day	90 days
Diethylene Glycol Monoethyl Ether	Ingestion	endocrine system	Not classified	Rat	NOAEL 2,500 mg/kg/day	90 days
Diethylene Glycol Monoethyl Ether	Ingestion	heart hematopoietic system nervous system	Not classified	Mouse	NOAEL 8,100 mg/kg/day	90 days
2-Butoxyethanol	Dermal	blood	Not classified	Multiple animal species	NOAEL Not available	not available
2-Butoxyethanol	Dermal	endocrine system	Not classified	Rabbit	NOAEL 150 mg/kg/day	90 days
2-Butoxyethanol	Inhalation	liver	Not classified	Rat	NOAEL 2.4 mg/l	14 weeks
2-Butoxyethanol	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 0.15 mg/l	14 weeks
2-Butoxyethanol	Inhalation	blood	Not classified	Rat	LOAEL 0.15 mg/l	6 months
2-Butoxyethanol	Inhalation	endocrine system	Not classified	Dog	LOAEL 1.9 mg/l	8 days
2-Butoxyethanol	Ingestion	blood	Not classified	Rat	LOAEL 69 mg/kg/day	13 weeks
2-Butoxyethanol	Ingestion	kidney and/or bladder	Not classified	Multiple animal species	NOAEL Not available	not available

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Page 9 **of** 12

12/06/18

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

General Transportation Statement: This product does not require classification by DOT, IATA, ICAO or IMDG.

Please contact the emergency numbers listed on the first page of the SDS for Transportation Information for this material.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact manufacturer for more information

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not applicable

Health Hazards

Acute toxicity

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	C.A.S. No	<u>% by Wt</u>
Diethylene Glycol Monoethyl Ether (GLYCOL	111-90-0	1 - 5
ETHERS)		
2-Butoxyethanol (GLYCOL ETHERS)	111-76-2	0.5 - 1.5

15.2. State Regulations

Contact manufacturer for more information

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact manufacturer for more information

15.4. International Regulations

Contact manufacturer for more information

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

Page 10 **of** 12

D180101 & D180105, Wheel & Paint Iron DECON (29-46C) 12/06/18

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 38-3347-2
 Version Number:
 1.03

 Issue Date:
 12/06/18
 Supercedes Date:
 10/09/18

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. Meguiar's, Inc. MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Meguiar's, Inc. product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a Meguiar's, Inc. product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Meguiar's, Inc. product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Meguiar's, Inc. provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, Meguiar's, Inc. makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from Meguiar's, Inc.

Meguiar's, Inc. USA SDSs are available at www.Meguiars.com

12