



# Product Bulletin



## WHITEWALL CLEANER

### Product Description:

Quickly cleans and brightens tires with whitewalls and white lettering. Also cleans black sidewalls, wheel wells, splash guards, rubber mats and cargo liners. Its blend of cleaners and surfactants remove dirt, oil, grease and road grime from tires and rubber in seconds. Concentrated for economy and versatility, it may be diluted up to 5:1 with water. Simply spray and rinse off. Leaves whitewalls sparkling white and showroom new. Safe for OEM/factory clearcoated wheels. VOC COMPLIANT.

### Product Details:

Non-Flammable  
VOC Compliant  
Water Base  
Body Shop Safe  
NPE Free  
Phosphate Free  
Concentrated  
pH: 12.5  
Color: Turquoise  
Fragrance: Floral

### Packaging:

Gallon: C-52  
5 Gallon Cube: C-52-5  
55 Gallon Drum: C-52-55



### Features & Benefits:

Cleans Brake Dust, Grease, Dirt, Dressing, New Tire Mold Release & Road Grime  
Spray On, Rinse Off Formula - Leaves No Residue  
Contains No Bleach

### Application: *Shake well before using. Read label before use. See SDS for more information.*

If wheels are hot, cool wheels with cold water rinse before applying product. Dilute as indicated. May be diluted up to 5:1 with water.

**Tire Cleaning:** Dilute up to 5:1 with water for normal tire cleaning applications.

**HD Tire Cleaning:** Dilute up to 2:1 with water for heavy duty tire cleaning applications. Clean one tire at a time. Apply using a pistol sprayer or a tank sprayer. Spray on surface and let sit for 30-60 seconds. Light agitation with brush or steel wool may be necessary on excessively dirty tires. Rinse thoroughly with high water pressure. Blow dry with air hose. Wipe dry with clean towel or blow dry with air hose.

### Helpful Tips:

Keep from freezing (32 °F/0 °C). Do not let dry on surface. Spray on using a drenching effect rather than a fine spray. Not recommended on aftermarket wheels with non-coated, polished, anodized or polished billet aluminum finishes. Always consult wheel manufacturer for care of delicate, aftermarket wheels before using this product, as staining may occur. Keep off aluminum and exterior painted surfaces.

### Safety Data Sheet:

GHS Compliant. SDS can be found online at [www.prowax.com](http://www.prowax.com).

## **BAF Industries**

1451 Edinger Avenue, Suite F, Tustin, CA 92780 and Florence, KY  
(800) 437-9893 • (714) 258-8055 • Fax (714) 259-1184 • [www.prowax.com](http://www.prowax.com)



INTERNATIONAL  
CARWASH  
ASSOCIATION®  
GROWING. SMARTER. TOGETHER.